

Load carriers

TRACTO
BT optio



Load carriers for Toyota Tracto N- & S-series Towing trucks

Shelf carrier



This design allows for sortation of items during the transportation process to allow organised distribution of goods.

The ends and shelves are reinforced to withstand loads up to 500 kg. The end uprights are held together by a top element. Lower shelf is recessed in the frame profile. Shelves reinforced with shelf supports. Upper shelves are continuously height-adjustable. Upper shelves have a 25 x 20 mm edge profile that creates a 10 mm high edge along the lateral sides. Max. load 500 kg. Lower shelf has a max. load of 500 kg. Available in different shelf sizes 800 x 600 mm (l x w) to 1600 x 800 mm (l x w).

Parcel carrier



For carriage of items of multiple size and shape, allowing secure and safe transportation.

The uprights are held together by a top element. Side gates are easily opened. The shelf is recessed in the frame profile. Max. load 500 kg. Two fixed wheels and two swivel wheels with grey elastic rubber tyres measuring 200 x 50 mm, ball bearing hubs. Available in different shelf sizes 1000 x 600 mm (l x w) to 1600 x 800 mm (l x w).

Platform carrier



A simple platform-style carrier designed to handle all type of goods, but requiring inherent stability when stacking items. Allows fast, easy and flexible transportation of goods.

The ends and shelves are reinforced to withstand loads up to 500 kg. The end uprights are held together by a top element. The shelf is recessed in the frame profile. Max. load 500 kg. Two fixed wheels and two swivel wheels with grey elastic rubber tyres measuring 200x50 mm, ball bearing hubs. Available in different shelf sizes 1000 x 600 mm (l x w) to 1600 x 800 mm (l x w).

Host carrier



This unit is designed to transport subsidiary load carriers such as dollies or other storage units on wheels. Particularly suited to production facilities they allow flexible load handling with the benefit of multi-load transportation.

Each host carrier can carry up to 600 kg. The number of carriers in a train depends on the truck's towing capacity, but the maximum weight per train is 2400 kg. The host carrier solution can be combined with other carriers from our wide range. Host carriers can carry either a full pallet dolly, or two half-pallet dollies. Depending on the customer's needs, the carriers can be built to accommodate different types of dollies, so as to increase efficiency and flexibility in material handling operations. Consult separate Fact Sheet for further information.

Load carriers for Toyota BT Optio N-series Orderpicking trucks

Step carrier

This model is ideal for order picking from higher levels, with a step-up facility combined with shelving for sortation in the process. This type of unit is specifically designed to dock with Toyota BT Optio N-series tractor units.

Trolley with steps for picking and replenishment in warehouse and production facilities. The combined solution provides an efficient mobile workplace, facilitating order picking up to a height of 3 metres. The uprights are held together by a top element. The lower shelf is recessed in the frame profile. Fixed distance between shelves. Available in different shelf sizes 800 x 600 mm (l x w) to 1600 x 800 mm (l x w).



Shelf carrier

This design allows for sortation of items during the transportation process to allow organised distribution of goods.

The ends and shelves are reinforced to withstand loads up to 500 kg. The end uprights are held together by a top element. Lower shelf is recessed in the frame profile. Shelves reinforced with shelf supports. Upper shelves are continuously height-adjustable. Upper shelves have a 25x20 mm edge profile that creates a 10 mm high edge along the lateral sides. Max. load 500 kg. Lower shelf has a max. load of 500 kg. Available in different shelf sizes 800 x 600 mm (l x w) to 800 x 1200 mm (l x w).



Parcel carrier

For carriage of items of multiple size and shape, allowing secure and safe transportation.

The uprights are held together by a top element. Side gates are easily opened. The shelf is recessed in the frame profile. Max. load 500 kg. Two fixed wheels and two swivel wheels with grey elastic rubber tyres measuring 200x50 mm, ball bearing hubs. Available in different shelf sizes 800 x 600 mm (l x w) to 800 x 1200 mm (l x w).



Platform carrier

A simple platform-style carrier designed to handle all type of goods, but requiring inherent stability when stacking items. Allows fast, easy and flexible transportation of goods.

The ends and shelves are reinforced to withstand loads up to 500 kg. The end uprights are held together by a top element. The shelf is recessed in the frame profile. Max. load 500 kg. Two fixed wheels and two swivel wheels with grey elastic rubber tyres measuring 200x50 mm, ball bearing hubs. Available in different shelf sizes 800 x 600 mm (l x w) to 800 x 1200 mm (l x w).



Options for Load carriers *(excl. Host carrier)*:

- Memo board
- Grid rail
- Shelf partition
- Pick train connection
- Side grid
- Extra shelves
- Other load carriers sizes on request
- Train solution



TP-Technical Publications, Sweden — 746804-040, version 2, 2017-03-28

TOYOTA

MATERIAL HANDLING